WD-1046*BD Washers



- Data is based on heater model and has nothing to do with non-heater model.
- 2) Data is based on American model(non-heater) and it could be different by power rating.

MODEL NUMBER CYLINDER		WD-1046*BD (Eagle)
Drum volume	cu.ft. (ℓ)	4.06 (99.7)
Diameter	in. (mm)	22.05 (560)
Depth	in. (mm)	16.08 (408.3)
Capacity	kg (1:10)	10
Max Washing Capacity	kg	13
DIMENSIONS & WEIGHT		
Height	in. (mm)	38 11/16 (983)
Width	in. (mm)	27 (686)
Depth	in. (mm)	29 3/4 (756)
Door Opening	in. (mm)	50 13/16 (129.1)
Weight: Net / Gross	lbs. (kg)	190 (86) / 205 (93)
SPEED		
Wash	RPM	45
Extract (High Spin)	RPM	1,000
G-force	G	312
ENERGY		
Electric Power Consumtion	HP(W)	2.68 (2,000) 1)
Total Energy Consumption per Cycle (DOE)		0.31 2)
	I IVVVII	2.45
Modified Energy Factor		2.45
WATER USAGE	/ (0)	12.00 (40.17)
Average Total Water Usage per Cycle		12.99 (49.17)
Average Hot Water Usage per Cycle		1.39 (5.27)
Average Cold Water Usage per Cycl		13.08 (49.52)
	psi(bar)	14.5-116(1-8)
NOISE & CYCLE TIME		
Noise Level (Sound Power)	dB	Lower than 64
Programme durations in minutes(Default	t) min	37
SYSTEM & CONTROL		
Inverter Direct Drive Motor		•
Intelligent Electronic Controls		•
3 Compartment Dispenser		•
Forced Drain System		•
WASH PROGRAMS		
Whites (Hot)		•
		•
Colors (Warm)		•
Delicates (Cold)		•
Permanent Press (Warm)		
Super Wash Added (Option)		•
COVENIENCE FEATURES		
End of Cycle Beeper		•
Door Lock Display		•
Self Diagnosis		•
Auto Balancing		•
Auto Sud Removal		•
Forced Drain System		•
Remaining Time Display		•
Status Indicator		•
4 Adjustable Leveling Legs		•
LoDecibel™ Quiet Operation		•
Coin Box Open Sensing		•
		<u> </u>
EXTERNAL FINISH		
Drum		NeveRust™ Stainless Steel Drum
Top Plate		Porcelain
Transparent Glass Window Door		•
Door Rim		Stainless Steel
Colors		White / Titanium
Cabinet		Painted Steel
Control Panel		Plastic (Silver Spray)
Window Display		Silk Screen
Window		Aluminum
CIRCUIT PROTECTION		Aluminum
		9 /220 40\//50\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
PCB fuse - Main Control Board	amps	8 (220-40V/50Hz) / 12 (120V/60Hz)
PCB fuse - Filter Assembly	amps	15
HOSE		
Inlet Hose Drain Hose	Ft. (mm) Ft. (mm)	4.92 (1,500) 6.56 (2,000)