

# GIANT-C & GIANT-C PLUS

## F1069FD\* Washers



<sup>1)</sup> Data is based on U.K non-heater model and it could be different by power rating.

<sup>2)</sup> Data is based on American model(non-heater) and it could be different by power rating.

MODEL NUMBER		F1069FD* (Giant-C & Giant-C Plus)
<b>CYLINDER</b>		
Drum volume	cu.ft. (ℓ)	4.2 (102.7)
Diameter	in. (mm)	22.05 (560)
Depth	in. (mm)	16.51 (419.3)
Capacity	kg (1:10)	10.2
Max Washing Capacity	kg	15
<b>DIMENSIONS &amp; WEIGHT</b>		
Height	in. (mm)	38 11/16 (983)
Width	in. (mm)	27 (686)
Depth	in. (mm)	30 1/5 (767)
Door Opening	in. (mm)	50 13/16 (1291)
Weight : Net / Gross	lbs. (kg)	190 (87) / 207 (94)
<b>SPEED</b>		
Wash	RPM	45
Extract (High Spin)	RPM	1,150
G-force	G	413
<b>ENERGY</b>		
Electric Power Consumption	HP(W)	0.67 (500) <sup>1)</sup>
Total Energy Consumption per Cycle (DOE)	KWh	0.36 <sup>2)</sup>
Modified Energy Factor		2.6
<b>WATER USAGE</b>		
Average Total Water Usage per Cycle	gal (ℓ)	12.87 (48.72)
Average Hot Water Usage per Cycle	gal (ℓ)	1.57 (5.93)
Average Cold Water Usage per Cycle	gal (ℓ)	12.61 (47.73)
Operational Water Pressure	psi(bar)	14.5-116(1-8)
<b>NOISE &amp; CYCLE TIME</b>		
Noise Level (Sound Power)	dB	Lower than 64
Programme durations in minutes(Default)	min	37
<b>SYSTEM &amp; CONTROL</b>		
Inverter Direct Drive Motor		•
Intelligent Electronic Controls		•
3 Compartment Dispenser		•
Forced Drain System		•
<b>WASH PROGRAMS</b>		
Whites (Hot)		•
Colors (Warm)		•
Delicates (Cold)		•
Permanent Press (Warm)		•
Super Wash Added (Option)		•
<b>COVENIENCE FEATURES</b>		
End of Cycle Beeper		•
Door Lock Display		•
Self Diagnosis		•
Auto Balancing		•
Auto Sud Removal		•
Forced Drain System		•
Remaining Time Display		•
Status Indicator		•
4 Adjustable Leveling Legs		•
LoDecibel™ Quiet Operation		•
Coin Box Open Sensing		•
<b>EXTERNAL FINISH</b>		
Drum		NeveRust™ Stainless Steel Drum
Top Plate		Porcelain (Single) Painted Steel (Stack)
Transparent Glass Window Door		•
Door Rim		Stainless Steel
Colors		White
Cabinet		Painted Steel
Control Panel		Steel
Window Display		Silk Screen
Window		Aluminum
<b>CIRCUIT PROTECTION</b>		
PCB fuse - Main Control Board	amps	8 (220-40V/50Hz) / 12 (120V/60Hz)
PCB fuse - Filter Assembly	amps	15
<b>HOSE</b>		
Inlet Hose	Ft. (mm)	4.92 (1,500)
Drain Hose	Ft. (mm)	6.56 (2,000)